OPUS® Column 36 cm Non-Wood Unpackaging

User Guide

UG-OPUS Column 36cm Non-Wood Unpackaging-01

The information contained in this document is subject to change without notice.

With respect to documentation accompanying Product Repligen makes no warranty, express or implied. Any and all warranties related to the documentation accompanying Product are expressly disclaimed. Customer shall refer to the terms and conditions of sale governing the transaction for any and all warranties for the Product.

Repligen Corporation shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent of Repligen Corporation.

Products are not intended for diagnostic or therapeutic use or for use in vivo with humans or animals.

For further information, please contact Repligen Corporation at www.repligen.com.

©2023 Repligen Corporation. All rights reserved. The trademarks mentioned herein are the property of Repligen Corporation and/or its affiliate(s) or their respective owners.

Customer Support

customerserviceUS@repligen.com

(800) 622-2259

Repligen Corporation

41 Seyon Street Building 1, Suite 100 Waltham, MA 02453 www.repligen.com

customerserviceEU@repligen.com

Repligen Europe B.V.

Hoeksteen 13 4815 PR BREDA

Contents

2. Read p	prior to opening crate				
Read prior to opening crate					
4. Index.	4. Index				
List of figures					
Figure 1.	Ramp and U-sheet				
Figure 2.	Tape and hook and loop				
Figure 3	Lid				
Figure 4.	Sidewalls				
Figure 5.	Collar				
Figure 6.	Collar				
Figure 7.	Ramp				
Figure 8	Resin sample hox				
Figure 9.	Removing support blocks				
Figure 10.	Attaching the ramp				
Figure 11.	Removing support blocks				
Figure 12.	Removing the column				

3

1. Introduction

The purpose of this guide is to provide instructions for removing an OPUS® 36R Pre-packed Column from a non-wood shipping container. Please read completely before beginning. For your safety, take note of the steps that require two people.

2. Read prior to opening crate

Caution: CASTERS ARE <u>LOCKED</u> IN 36R SHIPMENT. Immediately prior to rolling the column down the ramp, ensure casters are switched to the unlocked orientation by pressing on the caster lever.

- Red arrows indicate direction.
- Each crate is equipped with an attachable ramp (<u>Figure 1</u>, Number 1) for unloading the OPUS Column. The ramp is covered by the U--sheet (Number 2).

Figure 1. Ramp and U-sheet







3. Procedure

Step 1.

Remove all stretch wrapping and strapping from all sides of non-wood crate.

Step 2.

Cut open the four tapes on the bottom tray of the crate (<u>Figure 2A</u>) and fold down the flaps to expose the hook and loop strips (<u>Figure 2B</u>).

Figure 2. Tape and hook and loop





Step 3.

Remove crate top lid (Figure 3).

Figure 3. Lid



Step 4.

Lift and remove both sidewalls from crate base (Figure 4).

Figure 4. Sidewalls



Step 5.

Remove collar (Figure 5) from the column.

Figure 5. Collar





Step 6.

Remove the U-sheet from far-right (Figure 6).

Figure 6. U-sheet



Step 7.

Remove the ramp and lay on the ground facing the crate side with hook and loop strips (Figure 7).







Step 8.

If applicable, retrieve resin sample box located in front left corner of crate base (Figure 8).





Step 9.

With the casters <u>locked</u>, carefully tilt the column to the left, to the right, and backwards by supporting the black top cap and remove the L-shaped bottom support blocks (<u>Figure 9</u>).

Note: The rear L-shaped bottom support block is stationary and cannot be removed.


Figure 9. Removing support blocks



Step 10.

Fold up the ramp flap with hook and loop strips ($\underline{\text{Figure 10A}}$) and attach it to the crate flap with hook and loop strips ($\underline{\text{Figure 10B}}$ and $\underline{\text{C}}$).

Figure 10. Attaching the ramp





Step 11.

Unlock all four casters by pushing the levers up (Figure 11).

Caution: This step must be completed to avoid severe damage to the column and harm to personnel.

Figure 11. Casters



Step 12.

TWO OPERATORS are needed to remove the column from the crate. Slightly lift and push the column off the support beam (Figure 12A) and GENTLY roll it off the ramp (Figure 12B).

Caution: Do <u>NOT</u> grab the column by the white inlet and outlet ports on the black top cap.

Figure 12. Removing the column





Step 13.

Break down and dispose of all crate components in corrugated compactor or other traditional corrugated recycling streams.

4. Index

Casters			4,	14
Collar				8
Column				4
Ramn	4	10	13	14

Resin sample box	11
Safety	4
Sidewalls	7
Support blocks	12

Customer Service

Repligen Corporation 41 Seyon Street Waltham, MA, USA 02453

customerserviceUS@repligen.com

(781) 250-0111

repligen.com